



S.C. ITAL-KOL S.R.L.
RO, 307395 Commune of Şag, Str. XI nr. 64, Timiș county,
Romania,
Tel.: +40 256 395 200; +40 256 395 300, Fax: +40 256 395 100,
Vat no.: RO 6470443, Registration no. with the Trade Register:
J35 / 3176 / 93

CONSTRUIESTE
CORECT

Safety Data Sheet

Ed.1 /Rev.3 | Code F.14.00.05
Reviewed and supplemented on: 14.04.2011

PRIMER G 2022

Code 1. 5. 19

Type of product: Liquid primer coating based on synthetic resins, with a large capacity of penetrating the support.

Description of product: The PRIMER G 2022 primer coating represents a dispersion of synthetic resins, of blue colour.

Intended uses: The PRIMER G 2022 product is used inside and outside, as a primer for the absorbent supports on which the AUTOLIV PIANO 4 self-levelling foundation is to be applied.

Physical status	liquid
Colour	blue
Specific consumption	approx. 150 g/m ²
Operation temperature:	+ 5°C – + 35°C
Support layer temperature	+ 5°C

Usage manner: *The product is used only by trained and qualified operators, complying with the following stages:*

The PRIMER G 2022 product is used inside and outside, as a primer for the absorbent supports on which the AUTOLIV PIANO 4 self-levelling foundation is to be applied.

Before application, the support is inspected in order to see whether it is levelled, dry, defrosted, resistant, stable and clean, without dust, sediments, oils, fats, concentrated oil, crumbly parts.

The product is applied on the mineral supports used in constructions: concrete, light concrete.

The support surface is vacuumed and polished or swotted, as the case may be. The verification of coverage material adhesion to the support is recommended.

After checking the support layer, the content of the PRIMER G 2022 can is poured into a bucket, from where to be taken with the brush or the roller and spread on the support layer. Several layers shall be applied according to the degree of absorption of the support.

In case the product is applied on large surfaces, the content of the can shall be poured on the surface, it shall be spread with the rubber T, then it shall be levelled with the brush or the roller.

After usage, the tools shall be cleaned very well with water.

After priming, until the casting of the self-levelling foundation, attention shall be paid that the primed surface shall not be dusty or dirty. The forced drying shall be avoided through ventilation or high temperature.

After drying, the self-levelling foundation is cast.

Final recommendations:

- The PRIMER G 2022 product shall not be used on plastic, metal supports or on paint layers.
- No work shall be executed at temperatures under +5°C. High humidity and low temperatures delay the adherence time and hardening, while the high temperatures accelerate them.
- The product shall not be mixed with other materials.



S.C. ITAL-KOL S.R.L.
RO, 307395 Commune of Șag, Str. XI nr. 64, Timiș county,
Romania,
Tel.: +40 256 395 200; +40 256 395 300, Fax: +40 256 395 100,
Vat no.: RO 6470443, Registration no. with the Trade Register:
J35 / 3176 / 93

CONSTRUIESTE
CORECT

Safety Data Sheet

Ed.1 /Rev.3 | Code F.14.00.05
Reviewed and supplemented on: 14.04.2011

PRIMER G 2022

Code 1. 5. 19

Packaging: The product is packed in 5l and 25l cans.

Storage: The product is stored for max. 12 months in a dry place, in the original unopened package.

Marking: Each can has been marked on the basis with the manufacture date - five groups of digits symbolising:
day . month . year . number of manufacture lot.

Warranty: The product has a 12 month warranty from the manufacture date marked on the package, only under the storage conditions mentioned above.

Type of product: Liquid primer coating based on synthetic resins, with a large capacity of penetrating the support.

Note 1: The present data sheet accompanies each invoice or waybill which refers to the product presented in the sheet.

Note 2: It is forbidden to reproduce parts or fragments from the present data sheet.

Note 3: The present data sheet has been drawn up to properly inform the user about the presented product. The use of this sheet for other purpose than informing you about the product and preparing the technological specifications regarding application is strictly forbidden without the written consent of ITAL-KOL.

Note 4: For other additional information, which you consider you should receive or you find useful, we recommend that you contact the producer in writing, before using the product. Any producer liability regarding failures in applying the product resulted from misinterpreting the text of the present data sheet or from verbal consultancy is excluded.

Note 5: The data presented in the product data sheet and, mainly, the instructions regarding the manner and area of application of the product are based on the skills and practical experience of the person applying the product. Due to a large variety of materials, tools or working conditions which we cannot totally control or foresee or which, even if they are clearly mentioned in the product data sheet, are not correctly assessed by the person applying the product, in each case we recommend, before use, to carry out individual tests of applying the product, so that you can be sure that the product the present data sheet is describing is suitable for your respective field of application.

Any producer liability regarding failures in applying the product resulted from the causes mentioned above in this sheet is excluded, except for the event when the damages resulted only from the poor quality of the product that the present data sheet refers to.

Note 6: Depending on the evolution of the technical regulations applicable, the producer preserves the right to modify the present data sheet. For the purpose of confirming the data in the sheet, we recommend you to visit the web page: web www.italkol.ro prior to using the product